



All Rights Reserved, Copyright © June 2018, NEO Monitors AS

NEO Monitors LaserGas™ III ammonia analyzer (3rd generation) is specially designed for operation in hazardous areas and it provides real time in-situ NH₃ measurements for virtually any type of DeNO_x systems. The configuration is transmitter/receiver units for cross-duct/stack installation. An external junction (cable connection) box simplifies installation and maintenance. The operation principal is based on well proven Tunable Diode Laser Absorption Spectroscopy (TDLAS) implemented using fast scanning absorption technique with fully digital signal processing. Years of experience allowed us to carefully design this highly compact NH₃ analyzer which offers exceptional performance in harsh environments, is truly robust and provides immediate benefits in terms of operation ease and low cost ownership.

Features	Applications	Customer benefits
<ul style="list-style-type: none"> • In-situ real time measurements • Fast response time • Compact design • Low power consumption (< 10W) • TDLAS technology • Low detection limit • No interference from other gases • Not affected by high dust load • Lifetime calibration, no zero drift • Integrated span check • Additional H₂O measurements available • Ethernet connectivity • Suitable for SIL2 	<ul style="list-style-type: none"> • Selective catalytic reduction (SCR) • Selective non-catalytic reduction (SNCR) • Typical DeNO_x outlet • Emission monitoring <p>To;</p> <ul style="list-style-type: none"> • Refineries • Powerplants • Chemical industries • Petrochemical industries • Steel industries • and more 	<ul style="list-style-type: none"> • Reliable in-situ NH₃ measurements in real time • Process optimization • Reduction of NH₃/Urea consumption • Monitoring of catalyst activity • Increase DeNO_x efficiency and minimize emission • Simple installation, ease of use • Low maintenance cost • No consumables • No sampling systems • Compressed air purge (no need for Nitrogen) • No regular calibrations needed • Automatic span check available

LaserGas™ III SP NH₃ DeNO_x

Technical Data

Specifications	<p>Detection limit (NH₃): 0.2 ppm**</p> <p>Default range: 0 - 50 ppm</p> <p>Other ranges on request</p> <p>Range H₂O: 0 - 40% vol</p> <p>Max. process gas temperature: 500 °C</p> <p>Max. process gas pressure: 1.5 barA</p> <p>Optical path length: Typically 0.5 - 5 m***</p> <p>Repeatability: +/- 0.2 ppm or +/- 1 % relative, whichever is greater (application dependent)</p> <p>Linearity: < 1 % of range</p> <p>Response time: 1 second or longer (configurable)</p>	Ratings	<p>Power supply: 24VDC range 18-32 VDC Max. 10 W</p> <p>Power consumption : 4 - 20 mA output: 500 Ohm max. load impedance, not isolated</p> <p>Relay output: 1 A at 30 V DC/AC</p> <p>Safety</p> <p>Laser class: Class 1 according to IEC 60825-1, eye safe</p> <p>CE: Certified</p> <p>EMC: Conformant with directive 2014/30/EU</p>	<p>Purge flow: 5 -100 l/min (application dependent)</p>	
Environmental conditions	<p>Operating temperature: -40 °C to +65 °C (extended rating -40 °C to +65 °C on request)</p> <p>Storage temperature: -40 °C to +70 °C</p> <p>Protection classification: IP65</p>	Approvals	<p>IECEX/ATEX zone 1: II 2 G Ex d [op is] IIC T4 Gb (TU/RU) II 2 D Ex tb IIIC T78°C Db II 2 D Ex tb IIIC T88°C Db (Lasergas III Ext)</p> <p>CSA: Class I Div. 1, Groups B, C and D</p> <p>ATEX rating connection box: II 2 GD Ex e IIC T5 Gb -40°C ≤TA≤65°C</p>	Maintenance	<p>Calibration: Check recommended every 12 months</p>
Inputs / Outputs	<p>Analog output (3): 4-20 mA current loop (concentration NH₃, transmission, concentration H₂O)</p> <p>Digital output: 10/100 Base T Ethernet (Modbus TCP)</p> <p>Relay output (2): High gas, warning and fault (normally closed)</p> <p>Analog input: 4 - 20 mA process temperature and pressure reading</p>	Installation and Operation	<p>Flange dimension: DN50/PN10 or ANSI 2"/150 lbs (other dimensions on request)</p> <p>Alignment tolerances: Flanges parallel within 1.5°</p> <p>Purging of windows: Compressed dry and oil free air (recommended) or air blower</p>	Dimension and weight	<p>Transmitter and receiver unit (TU/RU): 215 mm (length, add 50 mm for purge unit) x 125 mm (diameter), 3.5 kg each</p> <p>TU/RU connection box: 260 mm x 160 mm x 90 mm, 2.5kg</p>
				<p>**NOTE: Detection limits are specified as the 95% confidence interval for 1 m optical path and gas temperature / pressure = 25°C / 1 barA. Measured in N₂.</p>	
				<p>*** Insertion tubes may be needed to shorten path length for very high dust loads.</p>	
				<p>Special process conditions on request.</p>	

*NEO Monitors reserve the right to change specifications without prior notice

Your local distributor:



neomonitors

NEO Monitors AS • Part of the Nederman Group • Prost Stabels vei 22 • N-2019 Skedsmokorset, Norway
Phone +47 67 97 47 00 • www.neomonitors.com